

Attention: Users of this BD Accuri[™] C6 Flow Cytometer

Before running samples:

- 1) Place an empty 12x75 mm tube on the SIP.
- 2) Click BACKFLUSH.
- 3) Place a *fresh* tube with 2 mL of filtered, deionized H₂O on the SIP.
- 4) Set time limit for 10 15 minutes and Fluidics speed to Fast.
- 5) Click RUN.
- 6) Once time limit is reached, click **DELETE SAMPLE DATA**.
- 7) Remove the tube and run samples.

After running samples:

- 1) Place a tube with 2 mL of diluted Decontamination Solution (#653154) (dilute per label instructions) on the SIP.
- 2) Select an empty data well.
- 3) Set time limit for 2 minutes and Fluidics speed to Fast.
- 4) Click RUN.
- 5) Once time limit is reached, remove the tube of Decontamination Solution.
- 6) Place a tube of 2 mL filtered, DI H₂O on the SIP.
- 7) Set a time limit of two 2 minutes.
- 8) Click **RUN**. The cytometer will stop automatically when the time limit is reached.
- 9) Leave the tube on the SIP until the cytometer is used again.

It is recommended that the system be shut down if it will not be run again that day.

Use only approved fluids, described in the Approved Reagents table of the BD Accuri C6 Flow Cytometer Instrument Manual

Research Use Only. Not for use in diagnostic or therapeutic procedures. Class 1 Laser Product.